

# NP-02US PDU

## TCP/IP Remote Power Management



NP-02US PDU provides intelligent remote power management operations, allowed by diversified ways to access and control including network protocols and local etc control mode, multistage system administrative privileges, network security account can be simple, rapid and reliable implementation of the power control, parameter monitoring and status of the equipment real-time detection.

Features	<ul style="list-style-type: none"> <li>● One USB console port &amp; one 10M/100M-T RJ45 Ethernet port, support AUTO-MDIX.</li> <li>● Support DHCP or static IP configure</li> <li>● Integrated SNMP agent and Trap notification message capability</li> <li>● POP3/SMTP for sending and receiving control commands or user data</li> <li>● Support password protecting user management, 8 user at most, and the port owner and access permission could be set</li> <li>● Support 2 ports control, and could be customized</li> <li>● Support port name, power on status and owner setting</li> <li>● User's software upgrading is available</li> </ul>
Functions	<ul style="list-style-type: none"> <li>● Web, Telnet, RS232, SNMP, Email management access</li> <li>● Support local/remote each port current, voltage, power, power factor revealed</li> <li>● Current alarm threshold by locale, email, trap methods</li> <li>● Event timers/clock for each power outlet.</li> <li>● Switch and reboot each outlets</li> <li>● Port reservation for different permissions.</li> <li>● Auto-ping for each power outlet by ICMP ping package, and can be reboot.</li> <li>● Simple internet firewall, forbid remote access illegally</li> </ul>

# Parameter

## NP-02US

Electrical parameter	
Enter Plug	1
Supply Plug	NEMA5-15P
Equipment end	IEC60320-C14
Outlets	(2) NEMA5-15R
Input Current	15 Amp
Input Voltage	110 VAC
Console Port	Baud rate:115200; 8 data bits ; No parity;1 stop bit, no hardware handshaking
Ethernet	10/100 Base-T, support AUTO-MDIX
Network Protocol	ICMP, IP, TCP/UDP, DHCP, Telnet, DNS, POP3/SMTP, SNMP, HTTP
Display	6LEDs
Other parameter	
Chassis	W: 0.59 " (150mm)
	D: 0.665 " (170mm)
	H: 1.75 " (44mm)
Operating Temperature	0°C – 50°C
Storage Temperature	-29°C – 60°C
Humidity	10-90% RH